

# Supreme Spirit X-Tender

## Specification

The craftsmanship and dedication that is implemented from our highly qualified manufacturing staff ensures your Caravan is designed, tested and produced with only the best resources.

<b>— CHASSIS</b>	
Chassis	Heavy duty Permagal:100mm(4") on single axle,150mm(6") on tandems
Base	Fully integrated chequer plate steel base (aluminium optional)
A Frame	extended to spring hangers 100mm(4") on single axle 150mm(6") on tandems
Axle	Single up to 4.57metres (15"), Tandem over 4.57 metres (15")
Brakes	Electric brakes on 300mm (12") drums
Wheels and Tyres	15" x 6 stud wheels 15" x 235 x 75 light truck radials
Safety Brakes	Electronic breakaway system to over 2000GVM
Stone guard	All aluminium chequer plate stone guard
Suspension Single	Supreme independent trailing arm coil and spring
Suspension Double	Simplicity load sharing independent trailing arm
Mudflaps	Standard
Corner Stabilisers	Drop down easy operation to each corner
Jacking Points	Located at both wheel arches
Jockey Wheel	200mm(8') diameter standard
Spare Wheel	Standard on bumper bar or underslung
Toolbox	steel toolbox and battery container standard
Jerry Can Holders	Standard
Water Tanks	1 x 80 litre standard 2 x 80 litre for shower vans
Wheel Arches	Welded steel and fully sealed
<b>— SHELL</b>	
Body	Smooth aluminium sides with stucco ends and roof
Boot	Front storage boot with external aluminium protection (where applicable)
Door	Entry door triple lock and separate security door (where applicable)
Door Light	Bargman light and grab handle combined
Roof Lifters	Ezy-Lift roof lifters standard to pop tops
Floor	Steel chequer plate floor and 300 mm high sides
Frame	Meranti frame screwed, glued and bolted
Gas Bottles	1 x 9 kg standard 2 x 9 kg to shower caravans
Grab Handles	1 to each corner of caravan
Hatches	1 x up to 4.88m (16') 2 x over 4.88m(16') (Mini Heki or 4 seasons)
Pressure Hatch	1 x standard
Insulation	Wool blend bats to ceiling polyester bats to walls
Lighting	12 volt lighting throughout
Power Points	240 volt throughout, 12 volt 1 x internal 1 x external
Water Connections	Main pressure inlet and waste water outlet
Water Tank Inlet	Lockable water tank inlet
Water Mains Outlet	Mains pressure tap on A Frame
Pressure Limiting	Pressure limiting valve to water inlet for shower vans
Windows	Glass windows standard
T.V. Point	Through the wall coax connector
<b>— INTERNAL</b>	
Beds-Double	Innerspring on lift up gas struts (where applicable)
Beds-Singles	Foam with lift up access lids
Bedsread	Standard to double beds only (where applicable)
Curtains	Light block out and pleated
Pelmets	Fabric Velcro attached
Terylenes	Standard

Dinette / Lounge	High density foam with lumber support
Drawers	All On rollers
Drawers	1 x end of dinette
Drawers	1 x under single beds
Drop Door	1 x end of dinette 1 x under longue
Cupboard doors	Timber framed, either painted or varnished
Floors	Vinyl throughout
Pantry	Roll out chrome pantry where applicable
Pots Drawer	Standard under mini grill
Porta-Potti-Provision	Under bed standard
Soap container	Standard at sink
Robes	Complete with drawer and built in dresser
<b>— APPLIANCES</b>	
Refrigerator	90 litre 3 way refrigerator standard
Cooker	4 burner cooker with separate grill
Microwave	20 litre or equivalent
Stereo	CD/Radio Player standard
Range hood	12 volt stainless steel range hood
Smoke Alarm	Standard
Fire Extinguisher	Standard
Sink	Deep bowl stainless steel sink (where applicable)
Clock	Battery operated clock
Battery Pack Consisting:	110 Amp heavy duty 12 volt battery maintenance free Battery retaining frame 6mm cable wired to auxillary and earth 240 volt power point to charger, Master switch Fused 12 circuit & 20 Amp circuit breaker
Low Voltage	Low voltage battery protector